



IC8 - VPX and Open VPX

This course covers the VPX and Open VPX VITA standards

Objectives

- Providing VMEbus-based systems with support for switched fabrics.
 - Describing the new 7-row high speed connector rated up to 6.25 Gbit/s.
 - Clarifying alignment and keying requirements.
 - Supporting PMC,FMC (VITA 57) and XMC (VITA 42) mezzanines.
 - Implementing Hybrid backplanes to accommodate VME64, VXS and VPX boards.
 - The course also explains the interoperability improvements offered by the Open VPX standard through the implementation of predefined system topologies.
 - This course has been delivered several times to companies developing defense and avionics equipments.
- A more detailed course description is available on request at training@ac6-training.com*

Prerequisites and related courses

- Basic knowledge of high-speed serial interconnect is recommended, such as PCIe, SRIO or Gigabit/10G Ethernet.
- See our courses on PCI Express reference [IC4 - PCI Express 3.0](#) course, RapidIO reference [IC5 - RapidIO 3.0](#) course, Gigabit Ethernet, reference [N1 - Ethernet and switching](#) course and 10 Gigabit Ethernet, reference [N3 - Ethernet 10 Gigabit](#) course

Plan

VPX STANDARD

- Objectives of this standard
 - Limitations of shared bus system
 - Implementation of a switch fabric
 - Evolutionary roadmap for VME users
- Overview, definitions
- System signals
 - Power supply
 - System controller
- Board form factor
 - Connector pin definitions, P0 utility connector
 - Alignment and keying
 - Electrical budgets for protocol standards
 - Power wafer current ratings
 - Connector pin definitions, P1
 - 3U modules, P2 connector, differential vs single-ended pinout

- 6U modules, P2-P6 connectors
- Backplane
 - Power delivery
 - Backplane fabric connections electrical requirements
 - System management signals connection
 - Hybrid backplane
 - Example: five slot fabric full mesh backplane routing

VME, SRIO, PCI EXPRESS AND ETHERNET ON VPX FABRIC CONNECTOR

- VME bus signals mapping on VPX
 - SYSRESET management
 - P3-P6 connector pin mappings
- Serial RapidIO on VPX fabric connector
 - Assigning Serial RapidIO ports to the VPX P1/J1 connector
- PCI Express on VPX fabric connector
 - Reference clock
 - System reset
 - Assigning PCIe ports to the VPX P1/J1 connector
- Gigabit Ethernet control plane on VPX fabric connector
 - 1000BASE-BX or 1000BASE-KX interface on each of the Ultra-Thin Pipe ports
- Gigabit Ethernet on VPX fabric connector
 - Pipe definition, Ethernet Fat Pipe 10GBASE-KX4, 10GBASE-BX4, Ultra Thin Pipe 1000BASE-KX, 1000BASE-BX

PMC/XMC REAR I/O FABRIC SIGNAL MAPPING ON 3U AND 6U VPX MODULES STANDARD

- Mezzanine card Rear I/O pattern maps
- Mezzanine Type label
- 3U vita 46.0 connector pin mapping
- 6U vita 46.0 connector pin mapping
- Electrical specifications

REAR TRANSITION MODULE

- General arrangement of front and rear modules
- Alignment keying sockets
- Current and power per RTM slot
- Connector pin definitions RP0

OPEN VPX

- Bringing versatile system architectural solutions to the VPX market
- Description of a series of standard profiles
- System Interoperability Diagram with interface content
- Profiles definition
- Backplane profile topologies: centralized, distributed, hybrid
- Mechanical requirements
- Slot profile
- Backplane profile
- Module profile
- Standard development chassis profile

Renseignements pratiques

Durée : 2 jours

Prix : 1350 € HT