

P5 - PPC476 core implementation

This course covers the PowerPC 476FP core, including L2 cache and PLB6 interface

Objectives

- A boot firmware that initializes the MMU has been developped.
- Internal debug facilities are described.
- The course focuses on PPC476 low level programming, especially the PowerPC EABI.
- Examples of exception handlers are provided.
- The course also covers the debug architecture.
- A FFT has been developed to explain how to use MAC instructions.
- The Floating Point Unit operation is described.
- Note that this course also includes the PLB6 interconnect.

Labs are compiled with GNU compiler and run under Lauterbach Trace32 debugger.

A more detailed course description is available on request at <u>training@ac6-training.com</u>

Prerequisites

• Experience of a 32 bit processor or DSP is mandatory

Course Environment

- Theoretical course
 - PDF course material (in English) supplemented by a printed version for face-to-face courses.
 - Online courses are dispensed using the Teams video-conferencing system.
 - The trainer answers trainees' questions during the training and provide technical and pedagogical assistance.
- At the start of each session the trainer will interact with the trainees to ensure the course fits their expectations and correct if needed

Target Audience

• Any embedded systems engineer or technician with the above prerequisites.

Evaluation modalities

- The prerequisites indicated above are assessed before the training by the technical supervision of the traineein his company, or by the trainee himself in the exceptional case of an individual trainee.
- Trainee progress is assessed by quizzes offered at the end of various sections to verify that the trainees have assimilated the points presented
- At the end of the training, each trainee receives a certificate attesting that they have successfully completed the course.
- In the event of a problem, discovered during the course, due to a lack of prerequisites by the trainee a different or additional training is offered to them, generally to reinforce their prerequisites, in agreement with their company manager if applicable.

Plan

INTRODUCTION TO PPC476FP

- Internal architecture overview
- Connection to peripheral IPs
- Clocking
- Programming model, the 4 register groups GPRs, SPRs, DCRs and memory mapped

INSTRUCTION PIPELINE

- 5-stage pipeline operation, 4-issue architecture
- Branch Target Address Cache
- Speculative execution, guarded memory
- Register renaming
- Serialization

EXCEPTION MECHANISM AND TIMERS

- Exception processing
- Critical versus non critical interrupts
- Syndrome registers updating according to the exception source
- Building the vector table
- Core timers: PIT, FIT and WDT
- Reset configuration

MEMORY MANAGEMENT UNIT

- Introduction to MMU, Process vs thread
- Unified Translation Lookaside Buffer organization
- Level 1 separate instruction and data TLBs, level 2 unified TLB
- Address translation
- Clarifying the purpose of the hash function
- Describing the Tag array
- Bolted entries
- MMU related exceptions
- UTLB coherency

L1 CACHES

- Cache basics
- 4-way set associative organization, LRU replacement algorithm
- Cache programming interface
- Cache related instructions
- Double line fetch enable
- Locking capability
- Cache control and debugging features
- Instruction cache synonyms

L2 CACHE

- Four-way set-associative level 2 cache design
- Modified/exclusive/shared/invalid, tagged, shared last, modified unsolicited (MESI+T+SL+MU) protocol coherencu
- Cache operation instructions
- Understanding how data / instructions are transferred from memory to L1 and L2 caches
- Preloading the L2 cache
- Reservation management
- L2 cache performance monitor

DATA PATH

- Clarifying the steps required to load a data cache line, utilization of refill buffers
- Use cases for lwsync, msync, mbar and eieio instructions
- Self-modifying code sequence
- Store gathering support

POWER INSTRUCTION SET ARCHITECTURE V2.05 COMPLIANT CORE

- Branch instructions, restrictions regarding regions that can be accessed by direct branches
- System call instruction: link between applications and RTOS
- Addressing modes
- Byte reverse instructions to access PCI/PCIe configuration space
- · Semaphore management with lwarx / stwcx. instructions
- · Arithmetical and logical instructions, shift and rotate instructions
- The PowerPC EABI
- Self-modifying code sequence
- 16-bit mac instructions to develop fixed point DSP algorithms

FLOATING POINT UNIT

- IEEE754 basics
- Six-stage super-pipelined floating-point arithmetic execution
- Floating point exceptions
- Data handling and precision

INTEGRATED DEBUG FACILITIES

- Invasive debug with JTAG
- Non invasive debug with trace port
- Hardware vs software breakpoints
- Range Inclusive / Exclusive Comparison Mode
- Data value comparison
- Debug related interrupts

HARDWARE IMPLEMENTATION OF THE PPC476FP CORE

- Clock and power management interface
- CPU control interface
- Reset interface
- External interrupt controller interface
- Instruction-side local bus interface
- Data-side local bus interface
- DCR interface

PLB6

- · Separate interfaces for masters, slaves and snoopers
- Supports SMP coherency, with 7 cache states
- Coherency State Transition Tables
- Coherent data intervention
- Command definitions, clarifying what is a RWITM, a RWNITC
- Transfer protocol, address phase
- Master Retry Requirements
- Hang Detect and Resolution Requirements
- Snoop Partial Response Requirements
- Ordering Requirements

Renseignements pratiques

Duration : 4 days Cost : 1950 € HT