

This course covers NXP QorIQ P1020/P1011, P1021/P1012, P1022/P1013, P1023/P1017, P1024/P1015, P1025/P1016

Objectives

- The course clarifies the architecture of the P102X, particularly the operation of the coherency module that interconnects the e500s to memory and high-speed interfaces.
- Cache coherency protocol is introduced in increasing depth.
- The e500 core is viewed in detail, especially the SPE unit that enable vector processing.
- The boot sequence and the clocking are explained.
- The course focuses on the hardware implementation of the P102X.
- A long introduction to DDR SDRAM operation is done before studying the DDR2/3 SDRAM controller.
- An in-depth description of the PCI-Express port is done.
- The course highlights both hardware and software implementation of gigabit / fast / Ethernet controllers.
- Communication interfaces are explained according to the exact reference of the SoC: either TDM or QuiccEngine or DPAA.
- AC6 has developed an optimized SPE based FFT coded in assembler language.
- Performance for 1024 complex floating point single precision samples is:
- 91_386 core clock cycles without reverse ordering, 94_124 with reverse ordering
- Performance for 4096 complex floating point single precision samples is:
- 470_778 core clock cycles without reverse ordering, 511_227 with reverse ordering
 For any information contact training@ac6-training.com

A more detailed course description is available on request at training@ac6-training.com

Prerequisites and related courses

- Experience of a 32-bit processor or DSP is mandatory.
- The following courses could be of interest:
 - Ethernet and switching, reference N1 Ethernet and switchingcourse
 - o IEEE1588, reference N2 IEEE1588 Precise Time Protocolcourse
 - PCI express gen2, reference <u>IC4 PCI Express 3.0</u>course
 - USB Full Speed High Speed and USB On-The-Go, reference IP2 USB 2.0 course
 - SD / MMC, reference IS2 eMMC 5.0 course

Course Environment

- Theoretical course
 - ^o PDF course material (in English) supplemented by a printed version for face-to-face courses.
 - Online courses are dispensed using the Teams video-conferencing system.
 - The trainer answers trainees' questions during the training and provide technical and pedagogical assistance.
- At the start of each session the trainer will interact with the trainees to ensure the course fits their expectations and correct if needed

Target Audience

• Any embedded systems engineer or technician with the above prerequisites.

Evaluation modalities

- The prerequisites indicated above are assessed before the training by the technical supervision of the traineein his company, or by the trainee himself in the exceptional case of an individual trainee.
- Trainee progress is assessed by quizzes offered at the end of various sections to verify that the trainees have assimilated the points presented
- At the end of the training, each trainee receives a certificate attesting that they have successfully completed the course.
 - In the event of a problem, discovered during the course, due to a lack of prerequisites by the trainee a different or additional training is offered to them, generally to reinforce their prerequisites, in agreement with their company manager if applicable.

Plan

INTRODUCTION TO P102X

SOC ARCHITECTURE

- Internal data flows, OCEAN switch fabric, packet reordering
- Implementation examples
- Address map, ATMU, OCEAN configuration
- Local vs external address spaces, inbound and outbound address decoding

e500 CORES

THE INSTRUCTION PIPELINE

- Dual-issue superscalar operation
- Execution units
- Dynamic branch prediction

DATA AND INSTRUCTION PATHS

- The Core Complex Bus
- Store miss merging and store gathering
- Memory access ordering
- Lock acquisition and import barriers

THE MEMORY MANAGEMENT UNIT

- The first level MMU and the second level MMU, consistency between L1 and L2 TLBs
- TLB software reload
- Process protection
- 36-bit real addressing

CACHES

- The L1 caches
- Software cache coherency
- Level 2 cache
- Allocation of data transferred by external masters into the cache: stashing
- e500 coherency module
- Snooping mechanism
- Stashing mechanism
- L2 cache locking

PROGRAMMING

- Differences between the new Book E architecture and the classic PowerPC architecture
- Floating Point units, Double-Precision FP
- Signal Processing APU (SPE)

EXCEPTIONS

- Book E exception handling
- Syndrome registers
- Core timers

DEBUGGING

- Performance monitoring
- JTAG emulation
- Watchpoint logic

INFRASTRUCTURE

RESET, CLOCKING AND INITIALIZATION

- Platform clock
- Voltage configuration selection
- Power-on reset sequence, using the I2C interface to access serial ROM
- Power management
- eSDHC boot
- eSPI boot ROM

e500 COHERENCY MODULE

- I/O arbiter
- CCB arbiter
- CCB interface

DDR3 SDRAM MEMORY CONTROLLER

- On-Die termination
- Calibration mechanism
- Mode registers initialization, bank selection and precharge
- Command truth table
- Hardware interface
- Bank activation, read, write and precharge timing diagrams, page mode
- ECC error correction
- Initialization routine

ENHANCED LOCAL BUS CONTROLLER

- Multiplexed or non-multiplexed address and data buses
- Dynamic bus sizing
- GPCM, UPMs states machines
- NAND flash controller

PCI EXPRESS INTERFACE

- 4-lane PCI Express interface
- Modes of operation, Root Complex / Endpoint
- Transaction ordering rules

• Programming inbound and outbound ATMUs

PROGRAMMABLE INTERRUPT CONTROLLER

- PIC in multiple-processor implementation
- Understanding interrupt masking
- Interprocessor interrupts
- Per-CPU register usage, message registers
- Nesting implementation

INTEGRATED DMA CONTROLLER

- Support for cascading descriptor chains
- Scatter / gathering
- Selectable hardware enforced coherency

PERFORMANCE MONITOR AND DEBUG FEATURES

- Threshold events
- Chaining, triggering
- Watchpoint facility
- Trace buffer

INPUTS/OUTPUTS

THE ETHERNET CONTROLLERS

- Address recognition, pattern matching
- Buffer descriptors management
- Physical interfaces
- Buffer descriptor management
- · 256-entry hash table for unicast and multicast
- Management of VLAN tags and priority, VLAN insertion and deletion
- Quality of service, managing several transmit and receive queues
- TCP/IP offload engine, filer programming
- IEEE1588 compliant time-stamping

ENHANCED SECURE DEVICE HOST CONTROLLER

- Storing and executing commands targeting the external card
- Multi-block transfers
- Moving data by using the dedicated DMA controller
- Dividing large data transfers

USB CONTROLLER

- EHCI implementation
- Periodic Frame List
- ULPI interfaces to the transceiver
- OTG support
- Endpoints configuration

SECURITY ENGINE

- Crypto channels
- Sequence to subcontract a crypto job to SEC
- Link tables
- Managing interrupts

LOW SPEED PERIPHERALS

- Description of the NS16552 compliant Uarts
- I2C controller
- Enhanced SPI controller

TDM INTERFACE (P1022/P1013 AND P1024/P1015)

- Serial interface
- Network mode of operation with up to 128 time-slots
- DMA configuration
- End-of-frame interrupt
- Configuring the TDM for I2S Operation

DISPLAY INTERFACE UNIT (P1022/P1013)

- Display interfaces
- Display color depth
- Pixel structure, alpha-blending
- Utilization of area descriptor
- Moving images through the dedicated DMA channel

QUICC ENGINE (P1021/P1012 AND P1025/P1016)

OVERVIEW OF QUICC ENGINE

- Integrated RISC CPU
- Communication between Host CPU and QE RISC CPU

INTEGRATED INTERRUPT CONTROLLER

- Priority management
- Steering the interrupt source to either Low priority or High priority input of the platform PIC

SYSTEM INTERFACE AND CONNECTION TO EXTERNAL COMMUNICATION PORTS

- Serial DMA
- QUICC engine external requests
- NMSI vs TDM
- Enabling connections to TSA or NMSI

BUFFER MANAGEMENT

- Utilization of Buffer Descriptors
- Chaining descriptors into rings
- Parameter RAM independent of protocol

UNIFIED COMMUNICATION CONTROLLERS

- UCC as slow communications controllers, UART mode
- UCC for fast protocols, virtual FIFOs

UCC HDLC CONTROLLER

- Flow control
- Setting global parameters
- Describing the parameter RAM

UCC TRANSPARENT CONTROLLER

- Transparent data encapsulation, frame sync and frame CRC
- Describing the parameter RAM

SERIAL INTERFACE

- Connecting TDM lines
- Parameterizing the timings related to Rx/Tx clock, sync and data signals
- Connecting the TDM line to UCC using Rx/Tx routing tables

MULTI-CHANNEL CONTROLLER ON UCC - UMCC

- Comparison with MCC and QMC
- Connecting time-slots to logical channels through Rx/Tx routing tables
- Implementing Rx/Tx channel buffers
- Interrupt management
- Channel-specific HDLC parameters
- Per channel exception management
- UMCC host commands

DATAPATH PROCESSING SUBSYSTEM (P1023/P1017)

DPAA OVERVIEW

- Definitions: buffer, buffer pool, frame, frame queue, work queue, channel
- Data formats
- Frame formats
- Packet walk through

QUEUE MANAGER

- Objectives if this accelerator
- Frame description
- Structure of frame queues
- Frame queue state machine
- Multiway resource arbiter
- Work queues and channels
- Enqueue and dequeue portals
- Class and intra-class scheduling rules
- Dequeue dispatcher operation
- Message ring
- Stash transaction flow control and scheduling
- Congestion avoidance
- CoreNet initiator scheduling and priority

BUFFER MANAGER

- Objectives if this accelerator
- Software portals
- Direct connect portals
- Software interface, Command register, Management Response registers
- Buffer Pool State Change Notifications
- Buffer pool size programming
- Performance Monitor

FRAME MANAGER

- Objectives if this accelerator, parsing, classifying and distributing in-line/off-line packet
- FMAN submodules
- Rx BMI features
- Tx BMI features
- Offline parsing, host command features
- Frame processing manager
- FMan controller
- Parser
- Key generator
- Policer

DATA PATH THREE-SPEED ETHERNET CONTROLLERS

- MAC address recognition
- 256-entry hash table for unicast and multicast
- Suspending the transmitter, handling pause packets
- RMON statistic counters, carry registers
- Client IEEE1588 timers

SECURITY ENGINE

- Job management using QMan interface
- Input / output rings
- Job descriptor parsing
- Sharing descriptors
- Selecting the authentication / cryptographic algorithm
- Public Key Hardware Accelerator (PKHA)
- SNOW 3G Accelerator
- Example, implementing IPSec

Renseignements pratiques

Inquiry : 6 days