



## IP3 - USB 3.0

**This course covers USB3.0 and related specifications: OTG 3.0, xHCI, UAS and AV classes**

### Objectives

- The course details the hardware implementation and clarifies the operation of 8b10b encoder/decoder.
  - All tests required to qualify the physical layer are detailed.
  - The course also covers the PIPE interface, which is used to interconnect the Link layer and the PHY.
  - A lot of sequences are used to explain the flow control mechanism, the error recovery mechanism and packet acknowledgment.
  - The dual operation of USB 2.0 and USB 3.0 is clarified, especially the initialization sequence used by the device to select the operation speed.
  - The course explains all requirements regarding low power management, particularly the consequences on hub design.
  - The enumeration is studied step by step.
  - The one-day part on xHCI, UAS and AV classes are covered on request only.
  - Note that this course is a mature course already delivered to main companies developing SoCs for wireless solutions.
- A more detailed course description is available on request at [training@ac6-training.com](mailto:training@ac6-training.com)*

### Prerequisites

- Knowledge of USB 2.0 is required, see our course reference [IP2 - USB 2.0](#) course
- For on-site courses, an additional day covering USB 2.0 fundamentals may be prepended to this USB 3.0 course.

### Course Environment

- Theoretical course
  - PDF course material (in English) supplemented by a printed version for face-to-face courses.
  - Online courses are dispensed using the Teams video-conferencing system.
  - The trainer answers trainees' questions during the training and provide technical and pedagogical assistance.
- At the start of each session the trainer will interact with the trainees to ensure the course fits their expectations and correct if needed

### Target Audience

- Any embedded systems engineer or technician with the above prerequisites.

### Evaluation modalities

- The prerequisites indicated above are assessed before the training by the technical supervision of the trainee in his company, or by the trainee himself in the exceptional case of an individual trainee.
- Trainee progress is assessed by quizzes offered at the end of various sections to verify that the trainees have assimilated the points presented
- At the end of the training, each trainee receives a certificate attesting that they have successfully completed the course.
  - In the event of a problem, discovered during the course, due to a lack of prerequisites by the trainee a different or additional training is offered to them, generally to reinforce their prerequisites, in agreement with their company manager if applicable.

## Plan

### SYSTEM ARCHITECTURE

- Dual-bus approach
- Dual simplex operation, concurrent IN and OUT transactions
- Explicitly routed packet traffic instead of USB 2.0 broadcast
- Multi-level link power management
- New features of data flow model
- Robustness

### DATA FLOW MODEL

- USB 3.0 transaction model
- Low power link state transitions
- Latency tolerance messaging
- Bus interval adjustment
- Link-level power management
- Super-speed packet format
- Bulk transfers, stream ID

### SOFTWARE ORGANIZATION

- Host Controller Driver, purpose of EHCI, xHCI
- USB driver
- Enumeration
- Client drivers
- Virtual communication between client drivers and endpoint through communication pipes
- Overview of UAS and Video Display new classes

### USB OTG 3.0

- Objectives of OTG specification
- Session Request Protocol
- OTG 2.0 Host Negotiation Protocol
- Impact on PHY layer, voltage thresholds and timeouts
- Impact on Link and upper layers
- Differences between OTG 2 and OTG 3
- Embedded Host
- OTG 3 Role Swapping Protocol
- Symmetry, SSPC-OTG
- Defining who is the default Host through Port capabilities

### PHYSICAL LAYER

- AC-coupled lines
- Receiver detection
- Low Frequency Periodic Signaling, utilization of LFPS
- Spread Spectrum Clocking
- 8b10b coding scheme
- Elasticity buffer
- Pre-emphasis, receiver equalization
- Lane polarity inversion detection
- Qualifying the physical layer, eye-diagrams
- Mathematical processing that must be performed in the oscilloscope
- Tests required by the USB Implementer Forum
- Loopback BERT

## **PIPE INTERFACE**

- Interface clocking and reset
- 16- or 32-bit data bus width
- Rx polarity
- Selecting transmitter voltage levels
- Rx status codes
- Clock tolerance compensation
- Transmitting and detecting LFPS
- Low power states

## **LINK LAYER**

- Flow control, header buffer credit
- Buffering for data and protocol layer informations
- Transmitter timers
- Packetization
- Specified encoded control sequences
- Packet replay in case of error detection
- Power-on reset, in-band reset
- Link training and status state machine, understanding the main important transitions
- Clarifying which transitions are required to enter test modes (loopback and compliance)

## **PROTOCOL LAYER**

- End-to-end communication rules
- Burst of back-to-back data packets
- End-to-end flow control, NRDY / ERDY transaction packets
- Link management packet
- TP sequences, highlighting differences with USB 2.0
- Host flexibility in performing isochronous transactions

## **HUB**

- Repeater / forwarder
- Routing outbound packets to explicit downstream ports
- Aggregating inbound packets to the upstream port
- Propagating time-stamp packet
- USB 3.0 new descriptors and requests

## **SUPER SPEED POWER MANAGEMENT**

- Power states of links, devices and functions
- Driving the power management policy
- Related in-band protocol mechanisms
- Inactivity timers
- Enabling remote wake sources

## **ENUMERATION**

- Device states
- Function suspend
- New commands: SetSel()
- Binary Device Object Store (BOS)
- SuperSpeed device capability
- Interface association
- SuperSpeed endpoint companion descriptor

**EXTENSIBLE HOST CONTROLLER INTERFACE (xHCI)**

- Host Controller hardware requirements
- Memory structures, buffer rings and TRBs
- Transfer ring, command ring, event ring
- Transaction scheduling
- Error detection and handling
- Device attachment / removal
- Utilization of doorbell
- Single Root I/O virtualization
- Debug capability

**UAS CLASS**

- Mass storage class specification
- SCSI architecture model
- Command queuing
- SAM-4 command identifier
- Transport protocol, command Information Unit
- Utilization of USB 3 streams
- Task management
- Transport protocol services
- Pipe usage class descriptor

**AUDIO / VIDEO CLASS**

- AV profile definition, Basic Device Profile
- AVCore, AVCluster, Hierarchy
- AVFunction, AVData
- Multi-channel audio
- Track selector
- Channel configuration
- TV set example
- Feature unit VideoControls
- Video Processing Unit
- AVControl interface
- AV synchronization types, asynchronous, synchronous, adaptive
- AV description document
- Request and control sequences, HDMI controls
- Support of HDCP 2

**Renseignements pratiques**

**Inquiry : 4 days**