



NS2 - MARVELL 88E6161 Ethernet switches

This course covers Marvell Link Street Gbps Soho switches

Objectives

- Providing the basic knowledge on 802.3 and 802.1.
 - Understanding the parameters that determine the QoS.
 - Implementing the Dynamic Queue Limit architecture.
 - Description of the Address Lookup engine.
 - Implementing the Distributed Switch Architecture.
 - Becoming familiar with the API defined by Marvell.
- This course has been delivered several times to companies involved in the design of embedded equipments.

Practical labs using the Marvell GUI allow attendees to understand the various operation modes offered by this class of switch devices.

A more detailed course description is available on request at training@ac6-training.com

Prerequisites

- Knowledge of IEEE 802.3 and IEEE 802.1: see our course Ethernet and switching, reference cours [N1 - Ethernet and switching](#)
- Knowledge of IEEE 1588 may also be needed: see our cours [N2 - IEEE1588 - Precise Time Protocol](#)

Environnement du cours

- Cours théorique
 - Support de cours au format PDF (en anglais) et une version imprimée lors des sessions en présentiel
 - Cours dispensé via le système de visioconférence Teams (si à distance)
 - Le formateur répond aux questions des stagiaires en direct pendant la formation et fournit une assistance technique et pédagogique
- Au début de chaque demi-journée une période est réservée à une interaction avec les stagiaires pour s'assurer que le cours répond à leurs attentes et l'adapter si nécessaire

Audience visée

- Tout ingénieur ou technicien en systèmes embarqués possédant les prérequis ci-dessus.

Modalités d'évaluation

- Les prérequis indiqués ci-dessus sont évalués avant la formation par l'encadrement technique du stagiaire dans son entreprise, ou par le stagiaire lui-même dans le cas exceptionnel d'un stagiaire individuel.
- Les progrès des stagiaires sont évalués par des quizz proposés en fin des sections pour vérifier que les stagiaires ont assimilé les points présentés
- En fin de formation, une attestation et un certificat attestant que le stagiaire a suivi le cours avec succès.
 - En cas de problème dû à un manque de prérequis de la part du stagiaire, constaté lors de la formation, une formation différente ou complémentaire lui est proposée, en général pour conforter ses prérequis, en accord avec son responsable en entreprise le cas échéant.

Plan

100 Mbps ETHERNET BASICS

- MAC layer, frame format, frame filtering
- Full duplex Ethernet vs CSMA/CD
- PHY layer, scrambling, 4b/5b coding, NRZI
- Auto-negotiation, utilization of FLPs
- MII

1 Gbps ETHERNET BASICS

- 1000BASE-T
- 1000BASE-X
- GMII transfer protocol, RGMII, SGMII

802.1Q BASICS

- Spanning tree algorithm, RSTP, MSTP
- VLAN tag, selecting one tree and selecting the priority of a frame
- Port states
- Automatic address learning
- Automatic address aging
- Handling multicasts, GVRP, IGMP snooping

INTRODUCTION TO 88E6161 SWITCHES

- Block diagram, ports 0-3 features
- Port 4 and port 5 operating modes
- Pin strapping
- Application examples

BASIC SWITCH FUNCTIONS

- MACs
- PPU
- RMON registers
- Basic switch operation
- 802.1X source address authentication
- Multiple FIDs in VLAN systems

NORMAL PORTS

- Ingress policy
- VLANs
- Special frame handling
- QOS qualification
- Port-based Ingress Rate Limiting
- Queue Controller
- Egress policy

PROVIDER PORTS

- Distinguishing S-TAG from C-TAG
- Customer-to-Provider traffic
- Provider-to-Customer traffic
- Customer-to-Customer traffic
- Provider-to-Provider traffic

DSA PORTS

- Implementing control traffic between switches and management CPU
- Forward DSA tag
- TO_CPU DSA tag
- FROM_CPU DSA tag
- Interconnecting switches by using cross-chip links
- Switch handling of DSA frames
- Secure Control Technology

ADVANCED SWITCH FUNCTIONS

- Spanning Tree support
- Ingress MGMT/BPDU frame detection
- Proper connection to a management CPU and to a router
- Port mirroring
- Port trunking support
- PTP implementation

ACCESSING SWITCH REGISTERS

- The 16 register groups
- Multi-chip addressing mode
- Single-chip direct access to registers
- Remote Management frames

PHY LAYER

- Transmit PCS and PMA
- Receive PCS and PMA
- Power management
- Far End Fault indication
- Auto MDI/MDIX crossover
- LED interface
- Accessing PHY registers, MDC/MDIO interface
- Auto-configuration

SOFTWARE ARCHITECTURE

- DSDT suite
- Multi-layer architecture
- OS independency
- Source code organization
- Platform specific routines
- SMI interface functions
- Switch driver layer
- API layer
- Interrupts

Renseignements pratiques

Renseignements : 3 jours